



Pos.	pcs	Description	Type-No./Contents	Remark
①	1	Cable mount angle plug	4449.93.8914.123(1073771)	Center pin CuBe (B)
②	1	SMA female, right-angle	4966.42.2420.025(1077001)	
③	1	cable	RG316/U (1124698)	Length 111.6±1
④	1	Heat shrink tube	∅ 3 black	Length 35 (A)
⑤				
⑥				

No. of cable		Pcs.	
--------------	--	------	--

Stripping dimension	Stripping dimension	Remarks
POS. ① 	POS. ② 	Pos. 1 Outer : Crimp \square SW 3.25 Inner : Soldering Pos. 2 Outer : Crimp \square SW 3.25 Inner : Soldering Frequency range: 300MHZ~900MHZ

	VSWR
	Insertion loss: 0.3dB
	Operation Temperature Range: -55°C~+85°C
	Impedance: 50 Ohm
	Proof Voltage: 300V/50HZ

		General Tolerance AA-CS-12	scale:	Customer: Cassidian Finland Customer drawing no:
		date	name	RF Cable Assembly
		generate	27.05.13 Luther Tang	
		checked	Norm Dony	
		Norm		
B	Add the remark	16.07.14 Luther	K-6812	Rev. B
A	Add the heat shrink tube	20.01.14 Luther		
nr.	rev.	alteration	date	name