




Product data sheet

IMS CONNECTOR SYSTEMS GmbH
 Obere Hauptstrasse 30
 D-79843 Löffingen
 Postfach 1141
 D-79840 Löffingen

Tel (+49) 7654 901-0
 Fax (+49) 7654 901-199
 Net: www.imscs.com
 E-mail: sales@imscs.com

Part Number: 5025.PSMP.1010.093 Description: PSMP p.c.b. mount plug "Limited detent"		Revision: b Date: 18.02.2013 Signature: R.Schwär Page: 1 of 2																																																																			
Design according to:	Power-SMP Spec. 119S000-000																																																																				
Electrical characteristics	<small>colored value means: still under test target value</small>																																																																				
	<table border="1"> <thead> <tr> <th>Value</th> <th>Unit</th> <th>Picture</th> </tr> </thead> <tbody> <tr> <td>Impedance (MIL-C- 39012B)</td> <td>50</td> <td>[Ω]</td> <td rowspan="10">  </td> </tr> <tr> <td>Operating frequency up to</td> <td>....10</td> <td>[GHz]</td> </tr> <tr> <td>Return loss</td> <td></td> <td></td> </tr> <tr> <td> 1 GHz</td> <td>40</td> <td>[dB]</td> </tr> <tr> <td> 2 GHz</td> <td>40</td> <td>[dB]</td> </tr> <tr> <td> 4 GHz</td> <td>33</td> <td>[dB]</td> </tr> <tr> <td> 6 GHz</td> <td>30</td> <td>[dB]</td> </tr> <tr> <td colspan="3">(Return loss depends primary on p.c.b. material + layout)</td> </tr> <tr> <td>3rd. Order PIM product 2x43dBm</td> <td>160</td> <td>[dBc]</td> </tr> <tr> <td>Insulation resistance</td> <td>≥ 5</td> <td>[GΩ]</td> </tr> <tr> <td>Insertion loss</td> <td>$\leq 0.03 \times \sqrt{f \text{ (GHz)}}$</td> <td>[dB]</td> </tr> <tr> <td>Contact resistance</td> <td></td> <td></td> </tr> <tr> <td> Centre contact</td> <td>≤ 3</td> <td>[mΩ]</td> </tr> <tr> <td> Outer contact</td> <td>≤ 2</td> <td>[mΩ]</td> </tr> <tr> <td>Contact current max. (DC)</td> <td>max. 1,2</td> <td>[A]</td> </tr> <tr> <td>Operating voltage</td> <td>480</td> <td>[V]</td> </tr> <tr> <td>Proof voltage</td> <td>1000</td> <td>[V]</td> </tr> <tr> <td>Power handling (at 20°C, sea level)</td> <td>≤ 200</td> <td>[W]</td> <td>at 2,2 GHz</td> </tr> </tbody> </table>	Value	Unit	Picture	Impedance (MIL-C- 39012B)	50	[Ω]		Operating frequency up to10	[GHz]	Return loss			1 GHz	40	[dB]	2 GHz	40	[dB]	4 GHz	33	[dB]	6 GHz	30	[dB]	(Return loss depends primary on p.c.b. material + layout)			3rd. Order PIM product 2x43dBm	160	[dBc]	Insulation resistance	≥ 5	[GΩ]	Insertion loss	$\leq 0.03 \times \sqrt{f \text{ (GHz)}}$	[dB]	Contact resistance			Centre contact	≤ 3	[mΩ]	Outer contact	≤ 2	[mΩ]	Contact current max. (DC)	max. 1,2	[A]	Operating voltage	480	[V]	Proof voltage	1000	[V]	Power handling (at 20°C, sea level)	≤ 200	[W]	at 2,2 GHz	<table border="1"> <thead> <tr> <th>Value</th> <th>Unit</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>Remarks</td> </tr> <tr> <td></td> <td></td> <td>at 910MHz / at 1870 MHz</td> </tr> </tbody> </table>	Value	Unit	Remarks			Remarks		
Value	Unit	Picture																																																																			
Impedance (MIL-C- 39012B)	50	[Ω]																																																																			
Operating frequency up to10	[GHz]																																																																			
Return loss																																																																					
1 GHz	40	[dB]																																																																			
2 GHz	40	[dB]																																																																			
4 GHz	33	[dB]																																																																			
6 GHz	30	[dB]																																																																			
(Return loss depends primary on p.c.b. material + layout)																																																																					
3rd. Order PIM product 2x43dBm	160	[dBc]																																																																			
Insulation resistance	≥ 5	[GΩ]																																																																			
Insertion loss	$\leq 0.03 \times \sqrt{f \text{ (GHz)}}$	[dB]																																																																			
Contact resistance																																																																					
Centre contact	≤ 3	[mΩ]																																																																			
Outer contact	≤ 2	[mΩ]																																																																			
Contact current max. (DC)	max. 1,2	[A]																																																																			
Operating voltage	480	[V]																																																																			
Proof voltage	1000	[V]																																																																			
Power handling (at 20°C, sea level)	≤ 200	[W]	at 2,2 GHz																																																																		
Value	Unit	Remarks																																																																			
		Remarks																																																																			
		at 910MHz / at 1870 MHz																																																																			
Mechanical characteristics	<table border="1"> <thead> <tr> <th>Value</th> <th>Unit</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td>Engagement force</td> <td>max. 45</td> <td>[N]</td> <td rowspan="4"></td> </tr> <tr> <td>Separating force</td> <td>min. 15</td> <td>[N]</td> </tr> <tr> <td>Mating cycles</td> <td>≥ 100</td> <td></td> </tr> <tr> <td>Center contact captivation</td> <td>≥ 7</td> <td>[N]</td> </tr> </tbody> </table>	Value	Unit	Remarks	Engagement force	max. 45	[N]		Separating force	min. 15	[N]	Mating cycles	≥ 100		Center contact captivation	≥ 7	[N]																																																				
Value	Unit	Remarks																																																																			
Engagement force	max. 45	[N]																																																																			
Separating force	min. 15	[N]																																																																			
Mating cycles	≥ 100																																																																				
Center contact captivation	≥ 7	[N]																																																																			

Product data sheet

IMS CONNECTOR SYSTEMS GmbH
 Obere Hauptstrasse 30
 D-79843 Löffingen
 Postfach 1141
 D-79840 Löffingen

Tel (+49) 7654 901-0
 Fax (+49) 7654 901-199
 Net: www.imscs.com
 E-mail: sales@imscs.com

Part Number: 5025.PSMP.1010.093	Revision: b
Description: PSMP p.c.b. mount plug "Limited detent"	Date: 18.02.2013
	Signature: R.Schwär
	Page: 2 of 2

Material & plating Housing Centre contact Insulator	RoHS (2002/95/EC) conform General: No magnetic nickel allowed in any of the materials.	
	Material	Plating
	brass brass PTFE	Ni-P + 0,15µm Au Ni-P + 0,15µm Au -

Environmental influences Operating temperature range Climatic sequence: 1. Dry heat 2. Damp heat, cyclic, 1 cycle 3. Cold 4. Damp heat, cyclic, 6 cycles	-65°C up to +165°C Standard	Remarks
	IEC 60068-2-61 IEC 60068-2-2-Ba IEC 60068-2-30-Db IEC 60068-2-1-Aa IEC 60068-2-30-Db	

Notes

Update historie		
Rev.	date	Signature
a	26.04.2013	R.Schwaer
b	21.06.2013	R.Schwaer